

# VINTAGE

APPLICATIONS Hospitality, Contract, Automotive, RV and Residential

Vintage is specifically formulated to emulate the appearance of fine waxed pull-up leather. It is designed to distress and lighten when it is sewn, tufted, stretched, or creased.

## GENERAL SPECIFICATIONS

**Width** 54"  
**Roll Size** 30 Yards  
**Thickness** 1.1 mm  
**Weight** 36 Ounces per Linear Yard  
**Backing** Polyester / Cotton

## PERFORMANCE SPECIFICATIONS

**Abrasion Resistance** 50,000+ Double Rubs per ASTM D 4157-92  
Wyzenbeek / CFFA-1A  
**Ultra Violet Resistance** 200 Hours per ASTM G26-96 Method C / CFFA-2  
**Cold Crack** -10° F Federal Standard No. 191A-Method 5874 / CFFA-6

## FLAMMABILITY REQUIREMENTS \*

California Fire Code Technical Bulletin No. 117, Section E  
UFAC Class 1  
BIFMA  
NFPA 260  
IMO A.652 (16) 8.2 and 8.3  
ASTM E84: Class 1 or A Rating  
May Comply with California 133 when Tested with Suitable Components

## CLEANING INSTRUCTIONS

Prompt cleaning is always recommended. Ordinary dirt and stains can be removed with a mild soap and water. Rinse the cleaned area with clean water and dry with a lint-free cloth. Vintage will resist, without serious discoloration, the repeated actions of normal dilutions of non-abrasive chlorine or ammonia-based cleaners.



202 SOUTH 12th STREET  
BIRMINGHAM, ALABAMA 35233  
LOCAL PHONE 205-322-3476 • WATS LINE 800-326-2726  
FAX 205-322-3484  
email - [mascofabrics@aol.com](mailto:mascofabrics@aol.com)  
[www.mascofabrics.com](http://www.mascofabrics.com)

\* This term and any corresponding data refer to typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions. 3.12